

To wash 30 baskets/hour. 350x350mm racks. Max. loading height: 220mm.

1301962





SALES DESCRIPTION

3 wash cycles. Cold rinse facility. Option of built-in water softener.

- √ GUARANTEED DISINFECTION in compliance with DIN 10534 Norm.
- √ THERMAL LOCK function: Sanitization quarantee. Ensures that the rinsing will be carried out only when the ideal temperature for disinfecting the dishes has been reached.
- ✓ Best performance.
- ✓ Optimal washing results.
- Sturdy and reliable.
- √ Stainless Steel, sturdy and resistant was-





FEATURES AND BENEFITS

- Intuitive use.
- Catering grade stainless steel construction.
- ✓ Double skinned door equipped with magnetic micro-switch and high-efficiency seal, ensuring thermal and acoustic insulation.
- √ Completely rounded, stainless steel wire rack support and guide.
- ✓ Electronic control panel with anti-moisture seal.
- √ Highly efficient stainless steel dispersers ensure optimum water distribution for enhanced washing results.
- Rinsing dispersers offer clean design. Assembly without screws.
- ✓ Double filter system provides effective wash pump protection.
- ✓ Independent rinse boiler complete with adjustable thermostat and thermal lock option.
- Easily removable dispersers and filters for cleaning and maintenance. No tools needed.
- Designed for guick and easy maintenance. Fast access to components for on-site maintenance.
- √ 100% tested.

INCLUDES

- ✓ Rinse aid pump.
- ✓ Detergent dosing equipment.
- 1 mixed basket.
- √ 1 small cutlery basket.

ACCESSORIES

- Stands for glass- and dishwashers
- Dosing equipments
- Manual water softeners
- Automatic water softeners
- □ 350X350 mm, baskets
- □ Inserts, supplements &
- √ 1 open basket.

- similar
- High Feet Kit
- ☐ Reverse Osmosis device OS-140P



Project	Date
Item	Qty





GLASSWASHER X-35 230/50/1 DD

To wash 30 baskets/hour. 350x350mm racks. Max. loading height: 220mm.

SPECIFICATIONS

Basket dimensions: 350 mm x 350 mm

Maximum glass height: 220 mm Cycle duration: 90 " / 120 " / 150 " Production baskets/hour: 40/30/24

Boiler capacity: 4.5 l Wash tank capacity: 12.7 I

Water consumption/cycle: 2.2 I

Electrical supply: $230 \text{ V} / 50 \text{ Hz} / 1 \sim (12 \text{ A})$

Plug: -

Loading

✓ Pump: 75 W / 0.1 Hp

√ Tank: 1500 W

√ Boiler: 2500 W

√ Total loading: 2575 W

External dimensions (WxDxH)

√ Width:420 mm

✓ Depth: 495 mm


✓ Height: 645 mm


Net weight: 31.5 Kg


Crated dimensions

485 x 590 x 690 mm

Gross weight: 34 Kg.









Project	Date
Item	Qty